

---

Subject: Re: How to run datawarrior on Linux  
Posted by [thomas](#) on Tue, 09 Jul 2019 11:31:59 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

I just tried to install DataWarrior on Centos7 using the current datawarrior for Linux installer v5.0.0.

First I confirmed that Java is installed by typing 'java -version'. The output was:

```
openjdk version "1.8.0_212"
```

```
OpenJDK Runtime Environment (build 1.8.0_212-b04)
```

```
OpenJDK 64-Bit Server VM (build 25.212-b04, mixed mode)
```

I unpacked the datawarrior500\_linux.tar.gz, opened a terminal, used 'cd' to navigate into the unpacked folder 'datawarrior\_linux'. Then I typed:

```
chmod 755 install.sh
```

```
su
```

```
./install.sh
```

to install datawarrior with superuser privileges.

After that I could start DataWarrior from the Applications/Office menu:

I also could open a test.dwar file with a double click. Can you verify that Java is installed properly with 'java -version'? If yes, then can you check, whether the /opt/datawarrior folder exists and whether you can start datawarrior from a terminal with '/opt/datawarrior/datawarrior'?

Thomas

### File Attachments

1) [dw in centos7.png](#), downloaded 1048 times

---