
Subject: How to run datawarrior on Linux

Posted by devendra.bcp@gmail.com on Mon, 08 Jul 2019 21:16:14 GMT

[View Forum Message](#) <> [Reply to Message](#)

I have installed datawarrior on my Centos 7 along with all necessary Java support. It is not clear to me how to run/start this tool before use. I tried with "module load datawarrior", but nothing come up to use.I have file test.dwar but it is not recognized by datawarrior.

Subject: Re: How to run datawarrior on Linux

Posted by [thomas](#) on Tue, 09 Jul 2019 11:31:59 GMT

[View Forum Message](#) <> [Reply to Message](#)

I just tried to install DataWarrior on Centos7 using the current datawarrior for Linux installer v5.0.0.

First I confoirmed that Java is installed by typing 'java -version'. The output was:

openjdk version "1.8.0_212"

OpenJDK Runtime Environment (build 1.8.0_212-b04)

OpenJDK 64-Bit Server VM (build 25.212-b04, mixed mode)

I unpacked the datawarrior500_linux.tar.gz, opened a terminal, used 'cd' to navigate into the unpacked folder 'datawarrior_linux'. Then I typed:

chmod 755 install.sh

su

./install.sh

to install datawarrior with superuser privileges.

After that I could start DataWarrior from the Applications/Office menu:

I also could open a test.dwar file with a double click. Can you verify that Java is installed properly with 'java -version'? If yes, then can you check, whether the /opt/datawarrior folder exists and whether you can start datawarrior from a terminal with '/opt/datawarrior/datawarrior'?

Thomas

File Attachments

1) [dw in centos7.png](#), downloaded 1281 times
