

---

Subject: Incorrect dearomatization of indazole structures

Posted by [Andrievs](#) on Tue, 30 Nov 2021 10:48:26 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

I am having issues with SD files where the structure is an indazole superstructure.  
I have attached a SD-file as examples with 3 structures.

The problem is that during the dearomatization process DataWarrior incorrectly places the double bonds resulting in a formation of s stereocenter.

See attached image for visual differences.

Is there a way to have the dearomatization be done correctly with out using additional software?

P.s. I am using DataWarrior version 5.5.0


Sincerely, Andrievs

### File Attachments


---

1) [indazole\\_aromatized.sdf](#), downloaded 557 times


2) [DataWarrior.png](#), downloaded 744 times



**Original  
aromatized form**



**Possible kekule  
form I**



**Possilbe kekule  
form II**

---

Subject: Re: Incorrect dearomatization of indazole structures

Posted by [thomas](#) on Tue, 30 Nov 2021 13:53:31 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hi Andrievs,

Your SD-File includes a non-standard Marvin extension that is not understood by DataWarrior:  
MRV\_IMPLICIT\_H

Marvin uses that feature to define explicit hydrogen atoms, which usually is not needed, because molfiles

usually are in a kekulized form. If, however, molfiles just contain bonds marked to be aromatic, the

Kekulizer needs more information, if multiple potentially protonated nitrogen atoms are present. Standard molfiles simply don't have a place to store that information. The only way to make your SD-files compatible would be to extend DataWarrior's molfile parser to support Marvin's non-standard extensions.

Hope this explains it, Thomas

---