## Subject: Incorrect dearomatization of indazole structures Posted by Andrievs on Tue, 30 Nov 2021 10:48:26 GMT

View Forum Message <> Reply to Message

I am having issues with SD files where the structure is an indazole superstructure.

I have attached a SD-file as examples with 3 structures.

The problem is that during the dearomatization process DataWarrior incorrectly places the double bonds resulting in a formation of s stereocenter.

See attached image for visual differences.

Is there a way to have the dearomatization be done correctly with out using additional software?

P.s. I am using DataWarrior version 5.5.0

Sincerely, Andrievs

## File Attachments

- 1) indazole\_aromatized.sdf, downloaded 475 times
- 2) DataWarrior.png, downloaded 549 times

Subject: Re: Incorrect dearomatization of indazole structures Posted by thomas on Tue, 30 Nov 2021 13:53:31 GMT

View Forum Message <> Reply to Message

Hi Andrievs,

Your SD-File includes a non-standard Marvin extension that is not understood by DataWarrior: MRV IMPLICIT H

Marvin uses that feature to define explicit hydrogen atoms, which usually is not needed, because molfiles

usually are in a kekulized form. If, however, molfiles just contain bonds marked to be aromatic, the Kekulizer needs more information, if multiple potentially protonated nitrogen atoms are present. Standard molfiles simply don't have a place to store that information. The only way to make your SD-files compatible would be to extend DataWarrior's molfile parser to support Marvin's non-standard extentions.

Hope this explains it, Thomas